



DecTec[®] PRODUCT PROFILE



THE PRODUCT ADVANTAGE

DecTec WBA 100 is a high strength adhesive that offers excellent field workability, and is compatible with all DecTec membranes.

WBA 100 adhesive is applied using a 1/16" x 3/32" V-notched trowel to porous substrates.

Membrane is placed into fresh wet adhesive resulting in faster installation times and higher production.

For additional information or MSDS sheets, please contact Skyline, toll-free at 1-866-461-3914 or www.dec-tec.com.

PRODUCT NAME: DecTEC WBA 100

FEATURES:

- Water base latex adhesive offers outstanding grab characteristics with good workability.
- For use with DecTec membrane over plywood substrates
- Low VOC

PACKAGING:

- 2.63 US gallons / 10 litres

TECHNICAL NOTES:

- Application Temperature:
Minimum 50 °F / 10 °C
- Weight: 30 lbs / 13.2 kg per pail
- Coverage: 300-390 sq. ft. per pail
- Shelf Life: 12 months
- Adhesive subjected to freezing must be discarded

NOTES:

This document is not an installation guideline. Applicators must fully read, or view our Installation Procedures, and have full understanding, prior to using or installing any of our products. Skyline will not be responsible for improper use or installation of our products.